




SARFB 200 SERIES

Light-Duty 3-Bolt Flange Block
Eccentric Lock



TURNER

Mounted Bearings

Available Seal Style:



Standard



Bearing Insert	Shaft Dia. d in. mm.	Dimensions in. mm.											Bolt Used in. mm.	Load Rating lbs. kN.		Bearing Insert	Housing Number	Weight lbs. kg.	
		A	E	I	G	B	L	S	Z	Y	Bi	N		M	Dynamic C _r				Static C _{0r}
SARFB 204-12	3/4	3.56	2.811	0.44	0.44	2.64	0.79	0.34	1.35	1.78	1.2205	0.2756	0.5709	5/16	2,883	1,496	SA 204-12	RFB 204	0.9
SARFB 204	20	90.5	71.4	11.1	11.0	67.0	20.0	8.7	34.5	45.25	31.0	7.0	14.5	M6	12.82	6.65	SA 204		0.4
SARFB 205-14	7/8	3.75	3.000	0.41	0.43	2.87	0.79	0.34	1.32	1.87	1.2402	0.2953	0.5709	5/16	3,155	1,810	SA 205-14	RFB 205	1.1
SARFB 205-15	15/16																SA 205-15		0.5
SARFB 205	25																SA 205		
SARFB 205-16	1																SA 205-16		
SARFB 206-17	1 1/16	4.45	3.563	0.47	0.47	2.99	0.87	0.41	1.52	2.22	1.4055	0.3150	0.6220	3/8	4,377	2,569	SA 206-17	RFB 206	1.3
SARFB 206-18	1 1/8																SA 206-18		0.6
SARFB 206	30																SA 206		
SARFB 206-19	1 3/16																SA 206-19		
SARFB 206-20	1 1/4																SA 206-20		
SARFB 207-20	1 1/4	4.82	3.937	0.50	0.50	3.50	0.94	0.41	1.65	2.41	1.5315	0.3346	0.6654	3/8	5,775	3,497	SA 207-20	RFB 207	2.0
SARFB 207-21	1 5/16																SA 207-21		0.9
SARFB 207-22	1 3/8																SA 207-22		
SARFB 207	35																SA 207		
SARFB 207-23	1 7/16																SA 207-23		

NOTE: Standard units include a regreaseable bearing. Non-regreaseable bearings are available upon request.